ALLAMA IQBAL OPEN UNIVERSITY

USMAN NOTES
www.usmannotes.com

Name:

Registration No.:

Course Code: 3477

Program: Bachelor

Semester: Autumn 2026

ALLAMA IQBAL OPEN UNIVERSITY, ISLAMABAD

(Department of Computer Science)

Course: Design Fundamentals (3477) • Level: Bachelor

Semester: Autumn 2026

Assignment No. 2

Total Marks: 100 • Pass Marks: 50

SOLVED ASSIGNMENT GUIDE — For Study & Reference

Note: This guide is prepared for study and reference purposes only. Students are advised to read the relevant units of the course book, understand the concepts, and then write the assignment in their own words. Copying this guide word for word is not allowed.

USMAN NOTES www.usmannotes.com

Question 1: The Time Model in Multimedia Systems and Its Importance for Synchronisation (20 Marks)

Question as printed: Define a time model in multimedia systems and explain its importance in synchronization.

Introduction

A text document does not care about time: its words are all present at once, and reading them faster or slower changes nothing about their meaning. Multimedia is different. A song played at the wrong speed changes pitch; a lecture video whose voice drifts away from the speaker's lips becomes hard to watch within a second; an animation, a set of slides and a commentary that fall out of step stop being one presentation and become three unrelated streams. Behind every

well-behaved multimedia system there is therefore an explicit answer to questions such as: what does 'at the same time' mean for a sound sample, a video frame and a subtitle? When exactly must each item be presented? What happens when the network delivers something late? That shared answer is the system's time model. This answer defines the time model of a multimedia system, describes its main components — timelines, timestamps, clocks and temporal relationships — and explains, with examples, why it is indispensable for synchronisation within one medium, between different media, and across a network.

What Is a Time Model? A Definition

A time model in a multimedia system is the formal framework the system uses to represent, schedule and coordinate time-dependent media: it defines a common time base (a clock), a time scale and units, points and intervals on timelines for each medium, and the temporal relationships that must hold between media items when they are presented. Put more simply, the time model is the set of rules that lets a system say 'this frame at 0.04 seconds, this sound sample beginning at exactly the same moment, this caption from 3.0 to 6.5 seconds' — and mean the same thing on the machine that created the presentation, the network that carries it and the machine that plays it. In the model, continuous media such as audio and video are treated as sequences of units (samples, frames) each with a presentation time, while discrete media such as text, images and user events are placed at points or intervals on the same timeline. Timing is commonly expressed with timestamps taken from a shared clock, and relationships such as before, after, meets, overlaps, during and simultaneous — the interval relations studied in logic — describe how clips and streams must line up.

Main Components of a Time Model

Four components appear in almost every practical time model. (1) A reference clock and time base: one authoritative progression of time against which everything is measured, with defined units (seconds, or media-specific units such as sample number and frame number) and a defined starting point. Systems often distinguish the timeline of the content as authored (the 'virtual' or presentation timeline) from the real wall-clock time of playback, and the model's job includes mapping one to the other when playback is paused, sped up or delayed. (2) Timelines per stream and a master timeline: each audio, video or caption stream has its own sequence placed on the shared master timeline, so the whole presentation is a coordinated set of parallel tracks — the picture used in every video editor. (3) Timestamps and durations: every unit carries the time at which it must be presented and, where relevant, how long it lasts; streaming protocols stamp packets for exactly this purpose. (4) Tolerance and correction rules: because real clocks drift and networks jitter, a usable model also states how much asynchrony is acceptable (for lip synchronisation, errors under roughly a tenth of a second are hard to notice; for two loudspeakers playing the same sound, the tolerance is far tighter) and what the player should do — drop a late video frame, briefly stretch audio, or re-synchronise — when reality departs from the schedule.

USMAN NOTES www.usmannotes.com




Figure 1: Separate media streams aligned on one shared timeline — the practical picture of a time model at work.

Table 1: Temporal relationships the time model must express

Relationship	Meaning	Example
Simultaneous (equal)	Two items presented at the same time	Lip movement and the spoken word; a drum beat and its visual flash
Sequential (before / meets)	One item follows another, with or without a gap	Question slide, then the worked-solution slide
Overlapping / during	One item runs inside or across another	Background music under a whole narration; captions during a speech
Parallel with offset	Streams start together but one is deliberately shifted	A translation voice-over starting a moment after the original speaker

Why the Time Model Matters for Synchronisation

Synchronisation is usually divided into three levels, and the time model serves all three. Intra-media (intra-stream) synchronisation concerns the timing within a single continuous medium: the frames of a video must appear at the authored rate — 25 or 30 per second, evenly — and audio samples must flow without gaps or doubling, or motion stutters and sound crackles. The time model supplies the schedule (each frame's presentation time) against which the player can detect and repair irregular delivery. Inter-media synchronisation concerns relationships between different media — the famous case being lip sync between the audio and video of a speaker, but also captions appearing with the words they transcribe, a pointer moving over a diagram as the narration mentions it, slides advancing with a recorded lecture, and sound effects matching game events. Without a common time base, each stream would run on its own clock and drift apart at its own rate; with one, the player can continually compare actual progress against the model and keep the streams locked. Inter-destination (or distributed) synchronisation extends the same requirement across machines and places: students watching a live class in different cities, or speakers in different rooms of a building, must hear and see events in step — again impossible without shared timestamps and a model for correcting clock differences.

The time model also quietly enables several everyday features. Seeking ('jump to 12 minutes 30 seconds') is only meaningful because every stream is indexed by the same timeline. Pause, slow motion and fast-forward are transformations of the mapping between the content timeline and real time, applied uniformly to all streams so they stay synchronised while their shared speed changes. Editing — cutting a scene — is timeline surgery whose correctness the model defines:

remove an interval from the master timeline and every stream loses the same interval. Live systems depend on it most of all: in a video call, audio and video arrive over a jittery network in packets stamped from the sender's clock, and the receiver uses a jitter buffer, holding packets briefly so they can be released exactly on schedule — a direct application of the time model, trading a little delay for synchronised, smooth playback. Where the model is absent or ignored, the symptoms are the ones every user knows: echoing double audio, voices trailing pictures, captions describing the previous scene, and presentations whose narration and slides part company.

- Definition in one line: a time model is the shared framework of clock, timelines, timestamps and temporal relationships by which a multimedia system schedules time-dependent media.
- Synchronisation has three levels — within a stream (even frame/sample timing), between streams (lip sync, captions, slides), and between destinations (many machines in step).
- Tolerances matter: lip-sync errors become noticeable around a tenth of a second; the model states the tolerance and the correction (drop, stretch, resync).
- Seeking, pause, speed change and editing are all operations on the model's timeline, applied to every stream together.
- Live systems implement the model with timestamps and jitter buffers to turn irregular packet arrivals into exactly scheduled playback.

Conclusion

A time model is the multimedia system's shared understanding of time: one clock, parallel timelines for the individual streams, timestamps and durations for every unit, explicit temporal relationships between items, and stated tolerances with corrections when reality drifts. It matters for synchronisation because synchronisation is impossible without something to synchronise to: the model is the reference that lets a player keep frames even, voices on lips, captions on words and distant viewers on the same moment. Every timeline in every editor, every timestamp in every streaming protocol and every jitter buffer in every video call is this abstract idea made practical.

Question 2: Main Objectives of Multimedia System Services (20 Marks)

Question as printed: What are the main objectives of multimedia system services?

Introduction

A multimedia system is more than a computer that can show pictures. Underneath the applications a user touches — the player, the lecture app, the video call — sits a layer of system services: the facilities provided by the operating system and its supporting software for creating, storing, processing, transmitting, synchronising, finding and presenting multimedia data. These services exist because multimedia data makes demands that ordinary data does not: it is huge, it arrives as timed streams rather than static files, several types must play together, and quality must hold up in real time or the experience collapses. This answer

explains the main objectives that those services are designed to achieve. The objectives can be grouped under seven headings — correct and timely handling of continuous media, synchronisation, integration of media types, efficient storage and retrieval, communication support, quality of service, and a usable environment for developers and users — and each is explained with the practical failure that occurs when it is not met.

Objective 1: To Handle Continuous Media Correctly and in Real Time

The first objective is to treat time-dependent media as streams with deadlines, not as ordinary data. A text file read a second late is merely a slow file; a video frame displayed a second late is a broken video. Multimedia services therefore aim to capture, process and present audio and video at their required rates continuously — scheduling processor time, disk access and memory so that data arrives 'just in time' and playback neither starves (buffer underflow, heard as stutter) nor floods. This objective drives real-time scheduling policies, buffering, and admission decisions in which a system refuses or degrades a new stream rather than ruining all the streams already playing.

Objective 2: To Synchronise the Media

Closely linked is the objective of synchronisation at all three levels: within a stream (even timing of frames and samples), between streams (audio with video, captions with speech, narration with slides), and between machines in distributed presentations. Services pursue this objective by providing common clocks, timestamping, synchronisation points and correction mechanisms, so application writers do not each have to reinvent lip sync. The success measure

is perceptual: the audience should never be able to tell that sound and picture travelled separately.

Objective 3: To Integrate Different Media Types into One Presentation

Multimedia means combination, so a central objective is integration: text, graphics, images, audio, video and animation must be storable in related structures, composable into a single presentation, and presentable together with consistent behaviour — one play button, one timeline, one seek operation acting on all components at once. Services support this with common data models, container formats and presentation engines, so that a course unit, an advertisement or a medical record can be authored, stored and delivered as one coherent object rather than a bundle of unrelated files the user must assemble by hand.

Objective 4: To Store, Organise and Retrieve Large Amounts of Media Efficiently

Media files are orders of magnitude larger than text, so services aim at efficient storage and retrieval: compression and standard formats to reduce size; file and database structures that can deliver streams at sustained rates; indexing by title, author, date and — increasingly — by content; and fast seeking into the middle of long recordings. A video library or a university's lecture archive meets this objective when a requested item starts playing almost immediately, at the requested point, without disturbing other users being served at the same time.

Objective 5: To Support Communication and Distributed Delivery

Most multimedia is consumed somewhere other than where it was made, so services aim to move media across networks within their timing budgets: streaming protocols that pace delivery to playback, adaptation to changing bandwidth (lowering resolution rather than

freezing), support for live and on-demand delivery, and multicast or content-distribution arrangements so a popular lecture or match can reach thousands without thousands of separate full streams from one server. Error handling belongs here too — deciding whether a lost packet is worth re-sending (for a file download, yes; for a live frame whose moment has passed, no).

Objective 6: To Guarantee and Manage Quality of Service (QoS)

Users experience multimedia as quality: resolution, smoothness, clarity, delay. A formal objective of the services is therefore to define, request, reserve and monitor quality of service — parameters such as bitrate, frame rate, maximum delay and jitter — negotiating between what the application wants, what the devices can do and what the network can deliver, and adapting gracefully when conditions worsen. In interactive services the objective includes keeping delay low: a conversation becomes unnatural when delay grows beyond a few hundred milliseconds, however beautiful the picture.

Objective 7: To Provide a Usable Platform for Authors, Developers and Users

Finally, services aim to make multimedia buildable and usable by people. For developers this means standard interfaces and tools — media frameworks, codecs, device abstractions — so an application works across cameras, microphones and screens without custom code for each. For authors it means editing, composition and authoring support. For end users it means simple, consistent control: play, pause, seek, volume, captions, speed — the same everywhere. Accessibility belongs to this objective as well: captioning, audio description and adjustable playback are services, not decorations. Security and rights management — who may view, copy

or alter a media object — are also commonly listed, since a service that cannot protect content will not be trusted with it.

Table 1: Objectives of multimedia system services — summary

Objective	What success looks like	Typical failure when absent
Real-time stream handling	Smooth, continuous playback and capture	Stutter, gaps, frozen frames
Synchronisation	Sound, picture, captions and slides in step	Lip-sync error, captions describing the previous scene
Integration of media	One presentation, one timeline, one control set	Loose files the user must assemble manually
Storage and retrieval	Instant start, fast seek, searchable archive	Long waits, unfindable recordings
Communication support	Reliable live and on-demand delivery that adapts to the network	Buffering wheels, collapsed live events
Quality of service	Agreed quality monitored and defended; graceful degradation	Sudden quality collapse under load
Usability, tools and protection	Standard controls and APIs; accessible; rights respected	Every app different; content unusable or unprotected

Conclusion

The objectives of multimedia system services all flow from one fact: multimedia data is large, timed, mixed and judged by human perception in real time. The services therefore aim to

handle continuous media against deadlines, synchronise streams within themselves, with each other and across machines, integrate all media types into single presentations, store and retrieve huge collections efficiently, deliver them across real networks, guarantee and adapt quality of service, and present developers, authors and ordinary users with a standard, accessible and protected platform. When these objectives are met, multimedia feels effortless; each objective on the list corresponds to a familiar frustration that appears the moment it is not.

Question 3: Key Multimedia Services and the Role of Window Systems in User Interaction (20 Marks)

Question as printed: List and briefly explain key multimedia services and the role of window systems in user interaction.

Introduction

When a student opens a learning app and watches a lecture — pausing it, turning on captions, shrinking it into a corner while taking notes, then sending a clip to a classmate — a dozen invisible services cooperate to make those simple actions possible, and one very visible system organises everything on the screen: the window system. This answer first lists and briefly explains the key services a multimedia system provides — the facilities for capture, storage, compression, synchronisation, presentation, communication, retrieval and interaction — and then examines the window system in detail: what it is, and the specific roles it plays in user interaction with multimedia, from overlapping windows and device-independent drawing to

event handling and the compositing that makes modern screens look and behave the way they do.

Key Multimedia Services, Listed and Explained

Capture and device services control the hardware — cameras, microphones, scanners, screens and speakers — hiding each device's peculiarities behind standard interfaces, so any application can record or play without custom code. Compression services (codecs) encode and decode audio, images and video (JPEG, MP3/AAC, H.264 and their successors), trading size against quality on demand. Storage services manage media files and databases: sustained-rate delivery for streams, huge-file handling, and metadata. Synchronisation services provide shared clocks, timestamps and scheduling so streams stay in step. Presentation and rendering services turn stored media into pixels and sound — drawing text and graphics, scaling and mixing video, spatialising audio — in cooperation with the window system described below.

Communication and streaming services move media across networks: protocols for live and on-demand streaming, bandwidth adaptation, buffering and error decisions appropriate to timed data. Retrieval and indexing services let users find media — by name and metadata, and increasingly by content (the subject of Question 5). Interaction services deliver user input — keyboard, mouse, touch, pen, gestures, voice — to the right application with timing information, and support the standard controls (play, pause, seek, volume) consistently. Composition and authoring services let creators assemble media into presentations with timelines and links. Finally, supporting services cover quality-of-service management, security and digital rights, format conversion (transcoding), and accessibility facilities such as caption

rendering and audio description. No single application could sensibly rebuild all of this; the services are the shared foundation that makes multimedia applications cheap to build and consistent to use.

- Capture/device services: standard control of cameras, microphones, scanners, displays and speakers.
- Compression services (codecs): encode/decode images, audio and video at chosen size and quality.
- Storage services: large-file and database handling with sustained delivery rates and metadata.
- Synchronisation services: common clocks, timestamps and scheduling that keep streams together.
- Presentation/rendering services: drawing, scaling, mixing and output of media to screen and speakers.
- Communication/streaming services: live and on-demand delivery with adaptation and buffering.
- Retrieval/indexing services: finding media by metadata and by content.
- Interaction services: routing keyboard, mouse, touch and voice input; standard media controls.
- Supporting services: QoS management, security and rights, transcoding, accessibility.

USMAN NOTES www.usmannotes.com

What Is a Window System?

A window system is the software layer that divides the screen into multiple rectangular regions — windows — each belonging to an application or document, and manages their creation, movement, resizing, overlap and destruction, the drawing inside them, and the delivery of input to them. Familiar examples are the Windows desktop environment, macOS's window server, and the X Window System and Wayland compositors of Linux; phones use the same ideas adapted to full-screen and split-screen apps. The window system sits between the hardware and the applications: applications ask it for a window and draw into it in device-independent terms, and the window system, with the graphics hardware, is responsible for what actually appears.

The Role of Window Systems in User Interaction

The first role is organising simultaneous activity. Multimedia work is inherently parallel — a lecture playing, notes being typed, a dictionary open, a chat arriving — and windows make that parallelism visible and manageable: the user arranges, overlaps, minimises and switches between tasks, and can compare sources side by side, which is a genuine study and work technique and not merely decoration. The second role is consistent interaction: because the window system supplies standard furniture — title bars, menus, buttons, scroll bars, dialogs — and standard behaviours, users learn one set of gestures and controls that work in every application; multimedia controls themselves (the seek bar, the volume slider, the full-screen button) live inside this consistent frame. The third role is input management: the window system decides which window is active, delivers keystrokes to it, routes mouse, touch and pen

events to the window under the pointer with correct coordinates, and handles focus changes — the invisible traffic direction without which simultaneous applications would steal each other's input.

The fourth role is controlled drawing and compositing. Each application draws into its own surface without knowing or caring what overlaps it; the window system (in modern systems, a compositor) assembles the final screen from all surfaces, adding shadows, transparency and smooth animation, and — vitally for multimedia — updating video regions at full frame rate while the surrounding windows stay still. This separation is also what makes picture-in-picture, video overlays and screen sharing possible: a video surface can be scaled, moved or captured because the window system, not the application, owns the final composition. The fifth role is device and resolution independence plus accessibility: applications draw in abstract units and the system maps them onto different screen sizes, pixel densities and multiple monitors, while system-level magnification, contrast and caption settings apply uniformly inside every window. In short, the window system is where multimedia becomes usable by a person: the services supply the media, but the window system supplies the desk on which all of it is laid out, arranged and touched.

Table 1: Window system roles in multimedia interaction

Role	What it does	Multimedia example
Organising tasks	Windows created, moved, resized, overlapped, minimised	Lecture video beside a notes document
Consistent interaction	Standard controls, menus and behaviours everywhere	Same play / seek / volume behaviour in every player

Input management	Focus and routing of keyboard, mouse, touch, pen	Typing goes to notes, clicks go to the player
Compositing	Assembles final screen from per-app surfaces; handles overlap and animation	Picture-in-picture video over a web page; screen sharing
Device independence & accessibility	Abstract drawing units; scaling across screens; system accessibility settings	Same app on laptop and projector; magnifier and captions apply everywhere

Conclusion

The key multimedia services — capture, compression, storage, synchronisation, presentation, communication, retrieval, interaction and their supporting facilities for quality, security and accessibility — form the engine room of every multimedia system. The window system is the room's public face: it organises simultaneous tasks into manageable windows, gives every application the same interaction language, directs input to the right place, composes the final screen from independent application surfaces at full video speed, and keeps the whole arrangement independent of the particular screen in use. Services make multimedia possible; window systems make it humanly usable.

Question 4: Multimedia and Hypermedia Data Models — Purpose and Description (20 Marks)

Question as printed: What are multimedia and hypermedia data models? Briefly describe their purpose.

Introduction

Every organised collection of information rests on a data model: a set of concepts for describing what the data is, how its parts relate, and what operations make sense on it. A bank's data model speaks of accounts, customers and transactions; a library's, of books, authors and loans. Multimedia needs its own models because its data refuses to behave like neat rows in a table: it includes continuous streams with timing, images whose meaning lies in their content and arrangement, sound, video, and documents meant to be explored by following links rather than read in one fixed order. This answer explains what multimedia data models and hypermedia data models are, describes the ideas each contributes — media objects and their attributes, temporal and spatial composition, and in the hypermedia case nodes, links and anchors — and states the purpose these models serve for the people who build, store, search and present multimedia.

Multimedia Data Models

A multimedia data model defines how multimedia data is represented, structured and manipulated in a system. Its basic unit is the media object — an image, an audio clip, a video segment, a text passage, a graphic — described not only by its raw content but by attributes

and metadata: media type, format, duration, dimensions, creation data, keywords and rights. On top of individual objects the model defines composition: how objects combine into a presentation in space (this picture beside that text, this video inside that region of the screen) and in time (this narration under that animation, this clip after that one, synchronised at these points), which is why multimedia models must represent intervals, durations and synchronisation relationships that ordinary data models never mention. They also typically describe content features used for searching — the colours and textures of an image, the transcript and topics of a recording — and operations proper to media, such as play from a point, scale, overlay and transcode. Object-oriented and object-relational databases, MPEG-7 description structures and the internal models of authoring tools are all instances of this idea: give every kind of media a first-class, describable place in the system.

Hypermedia Data Models

A hypermedia data model adds the dimension of navigation to a multimedia model. Where a multimedia model may describe a fixed presentation, a hypermedia model describes a network to be explored: its central concepts are the node (a unit of content — a page, a clip, a definition — corresponding to the media objects above), the link (a typed, directional connection from a source to a destination expressing a relationship such as 'explains', 'shows an example of', 'is the next step to'), and the anchor (the exact point within a node — a word, a button, a region of an image, a moment in a video — from which a link departs or at which it arrives). Classic reference models such as the Dexter Hypertext Reference Model formalised exactly these ideas: a storage layer of components and links, a within-component layer for anchors and content, and a run-time layer for presentation and following links. The World Wide Web is the

largest hypermedia model in daily use, with pages as nodes, URLs as addresses, and HTML anchors as links — a deliberately simple instance of the general model; richer systems add typed links, two-way links, link contexts and guided tours (author-suggested paths through the network).

Table 1: Multimedia and hypermedia data models compared

Aspect	Multimedia data model	Hypermedia data model
Central question	What media exists, and how is it composed in space and time?	How is media connected, and how does a user navigate it?
Key concepts	Media objects, attributes/metadata, spatial and temporal composition, synchronisation	Nodes, links (typed, directional), anchors, paths/tours
Typical structure	Compositions and presentations with timelines	A network (graph) of linked nodes
User's experience	A presentation that plays or displays as authored	Exploration: the user chooses the route
Examples	Multimedia database schemas, MPEG-7 descriptions, authoring-tool document models	Dexter reference model; the Web (HTML pages, anchors, URLs); linked courseware

USMAN NOTES www.usmannotes.com

The Purpose of These Models

The purposes of the two models overlap and reinforce each other. First, organisation and management: the model gives a system a principled way to store millions of heterogeneous media objects so that they can be catalogued, updated, reused in new presentations and kept consistent, instead of surviving as anonymous files in folders. Second, retrieval: because objects carry structured descriptions and content features, and hypermedia adds typed links between them, users can find material both by searching and by following meaningful paths — 'everything about this topic, then its examples, then its exercises' is a route through a model, not a lucky accident. Third, presentation and navigation support: the model is the contract the player or browser works from — composition and timing rules in the multimedia model tell it how to lay out and synchronise a presentation, while nodes, links and anchors tell it what can be selected and where selection leads. Fourth, interoperability and longevity: systems that share a model can exchange content (as the Web's simple model lets any browser render any site), and content described by a model outlives the particular application that created it. Fifth, authoring support: models give authors reusable patterns — a node type for 'worked example', a link type for 'prerequisite' — so large courseware, manuals and archives can be built consistently by teams over years. A useful way to summarise the division of labour is that the multimedia data model describes what the content is and how it is put together, and the hypermedia data model describes how it is connected and travelled through; a complete modern system, from a streaming library to an online course, needs both.

- Multimedia data model: media objects + attributes + spatial/temporal composition + synchronisation + content features for search.

- Hypermedia data model: nodes + typed directional links + anchors, arranged as a navigable network (Dexter model; the Web as the everyday instance).
- Shared purposes: organisation and reuse, retrieval by search and by navigation, correct presentation, interoperability and longevity, and consistent team authoring.

Conclusion

Multimedia data models define how media objects and their timed, spatial compositions are represented and managed; hypermedia data models extend that foundation with nodes, links and anchors so the collection becomes a network a user can explore. Their purpose is practical, not decorative: they make vast mixed collections storable, searchable, presentable, exchangeable and authorable — the difference between a warehouse of unrelated files and a library. Every course portal, streaming catalogue and electronic reference work a student uses is these two models at work, whether or not the student ever sees their names.

Question 5: Content-Based Retrieval; The Role of Network Protocols in Multimedia Communication (20 Marks)

Question as printed: a) What is content-based retrieval in multimedia systems? b) What role do network protocols play in multimedia communication?

Introduction

Two problems decide whether networked multimedia is actually usable. The first is finding things: a collection may hold a million photographs, lectures and songs, but they are worthless to a user who cannot locate the one item needed — and media, unlike text, cannot simply be

searched by the words inside it, because a photograph contains no words at all. The second is delivery: even the right item is useless if it arrives too late, in the wrong order, or out of step with its soundtrack. Part (a) of this answer explains content-based retrieval — searching for media by what it actually contains — and part (b) explains the role of network protocols, the agreed rules that carry multimedia across networks with the timing, order and quality it requires.

Part (a): What Is Content-Based Retrieval?

Content-based retrieval is the technique of searching a multimedia collection using the content of the media itself — the colours, shapes and textures of images; the melody, rhythm and sound character of audio; the scenes, motion and spoken words of video — rather than relying only on manually attached names, titles and keywords. In a content-based image retrieval (CBIR) system, for example, each picture in the collection is analysed in advance and its features stored in an index: a colour histogram recording how much of each colour it contains, texture measures describing surfaces such as smooth, striped or grainy, and shape descriptors of its main regions. A user then searches by example (supplying or sketching a similar picture), by feature ('mostly green, outdoor, people'), or by a hummed phrase or spoken phrase for audio; the system extracts the same features from the query, compares them with the index using a similarity measure, and returns the closest matches ranked by similarity — near-duplicates and near-misses included, which is exactly what a human browsing visually would want.

For audio and video the same principle extends naturally: speech in recordings is transcribed automatically so the spoken content becomes searchable; music is fingerprinted so a few

seconds recorded in a noisy shop can identify the song; video is divided into shots, key frames are analysed like images, faces and objects are recognised, and on-screen text is read — one video becomes searchable from many directions at once. Content-based retrieval matters because manual annotation cannot scale and cannot be trusted: nobody will ever keyword a billion photographs, uploaders describe their own files carelessly or not at all, and some qualities ('a tune like this', 'a fabric that feels woven') are easier to show than to say. Its known weakness is the semantic gap: low-level features are not meaning. A system can find every picture dominated by red and blue without knowing which are sunsets and which are flags; modern systems narrow the gap with object recognition, learned features and relevance feedback, in which the user marks results 'more like this / less like this' and the search refines itself. The familiar everyday instances — searching a phone's photo library for 'beach' or 'documents' without having labelled anything, identifying a song from a fragment, finding every scene containing a person in a video archive — are content-based retrieval in daily service.




Figure 1: Content-based retrieval — a query's features are extracted and matched against indexed features of the collection, and results are ranked by similarity.

Part (b): The Role of Network Protocols in Multimedia Communication

A network protocol is a standardised set of rules — message formats, sequences and behaviours — that allows two systems to communicate. For multimedia, protocols do far more than move bytes: they carry timing, repair or conceal damage, adapt to changing conditions and keep separate streams in step. Their roles can be grouped as follows. (1) Transport with the right trade-offs: ordinary data uses TCP, which guarantees delivery by retransmission — correct for a file, but a retransmitted video frame often arrives after its moment has passed; multimedia therefore commonly uses UDP-based transport (with RTP, the Real-time Transport Protocol, running over it), accepting occasional loss in exchange for timeliness, with each packet carrying sequence numbers and timestamps. (2) Timing and synchronisation: RTP timestamps and its companion RTCP reports let receivers reconstruct the sender's clock, measure delay, jitter and loss, synchronise audio with video and even synchronise receivers with each other; the timestamps are the time model of Question 1 travelling on the wire.

(3) Session control: protocols such as RTSP (for play, pause and seek on streamed media), SIP and WebRTC's signalling (for setting up calls and conferences) establish, manage and close multimedia sessions, negotiating which codecs and rates both ends support. (4) Adaptation and quality: modern delivery (HTTP-based adaptive streaming such as HLS and MPEG-DASH, and WebRTC in calls) monitors the connection and switches between prepared quality levels, while underlying mechanisms request bandwidth, mark priority traffic and report congestion — protocols are how quality of service is requested, signalled and enforced between applications, routers and servers. (5) Addressing, naming and delivery structure: URLs identify media objects; content-delivery arrangements and multicast protocols distribute one popular stream

efficiently to many receivers; and security protocols encrypt the media and authenticate the parties, so calls and paid content are private. Remove protocols and each application would have to invent private arrangements for all of this with every partner — the practical meaning of 'protocol' is that a player, a server and a network built by strangers can still cooperate to deliver one synchronised, adaptive, secure presentation.

Table 1: Protocols and their multimedia roles (examples)

Protocol / family	Layer of the job	Role in multimedia communication
UDP	Transport	Fast, lightweight delivery where timeliness beats perfect reliability
RTP / RTCP	Application (over UDP)	Carries timed audio/video with sequence numbers and timestamps; reports quality and aids synchronisation
RTSP	Application	Remote control of streaming: play, pause, seek
SIP / WebRTC	Application	Sets up and manages calls and conferences; negotiates codecs; WebRTC carries encrypted real-time media in browsers
HLS / MPEG-DASH (over HTTP)	Application	Adaptive on-demand and live streaming: switches quality with

		bandwidth
TCP / HTTP	Transport / application	Reliable delivery for files, web pages and buffered (non-live) media

- Content-based retrieval in one line: search by the media's own features — colour, texture, shape, melody, fingerprint, transcript — ranked by similarity.
- Why it is needed: manual keywords cannot scale, are unreliable, and cannot express 'like this tune / picture'.
- Its weakness is the semantic gap between low-level features and human meaning, narrowed by recognition techniques and relevance feedback.
- Protocols provide: timely transport, timestamps and synchronisation, session control, quality adaptation, addressing/efficient distribution, and security.

Conclusion

Content-based retrieval solves the finding problem of multimedia: collections are indexed by automatically extracted features of the media itself, queries are matched by similarity, and results are ranked — letting users search photographs, music and video by what they contain rather than by what somebody once called them. Network protocols solve the delivery problem: they transport timed media with the right balance of speed and reliability, carry the timestamps that make synchronisation possible, set up and control sessions, adapt quality to real networks, address and distribute content efficiently, and keep it secure. Finding and

delivery — retrieval and protocols — are the two halves that turn stored media into a working multimedia service.

USMAN NOTES
www.usmannotes.com